



For a confined space clearance measurement, a sampling hose is attached to a pumped gas detector. An open end of runs the risk of allowing dust and liquids to enter the sampling hose, blocking the hose and delaying the work. Ball floats are a perfect way to ensure no liquid or dust can enter the sampling hose.

WatchGas has completely redeveloped the ball float to make it suited to heavy duty work in every way.

The ball float is made in one piece to make it more resistant and durable in comparison to ball floats that are made from two hemispheres glued together. The material is chemical-resistant, antistatic and non-adsorbent, so as not to interfere with your measurement. Also, its bright yellow color makes it visible, providing contrast in dimly-lit situations.

We believe we have developed the best ball float. But the best part is that it's very competitively priced. Give us a call or visit our website to find the nearest distributor.

Specifications	Ball Float
Dimensions	60 x 65 mm
Material	High Density Polyethylene
Conformity	IEC/TS 60079-32-1:2015, IEC 61340-4-4, Nationaler Brandschutz NFPA 77 (2013) / EN-60079-0
Suitable for	3x5 mm Sampling Hose 5x8 mm Sampling Hose

Specifications	Sampling Hose
Dimensions	3x5 mm (Art.Nr. 411 0018 038) 3x8 mm (Art.Nr. 411 0018 039)
Hardness	60 - 65 Shore A
Density	2.01 ± 0.03 g / cm ³
Tensile Strength	8 N/ mm ²
Elongation	280%
Resistance	8%
Shape Retention	20%
Temperature Resistance	24 hours / 175° C -18° C to +200° C
Short-Term Heat Resistance	+ 250° C
Protection Against Electrostatic Discharge	NEN / EN / IEC 61340-5-1: 2016



For more information

www.watchgas.nl

info@watchgas.nl

WatchGas

Sextantstraat 61
2908 ZZ Capelle aan den IJssel
+31 (0) 85 - 0187709
The Netherlands



Distributed by